

Silkolene®

SILKOLENE COMP 4 XP RANGE Extreme Performance Semi-Synthetic Ester Engine oils

Description

The SILKOLENE COMP 4 XP range of motorcycle engine oils are designed using XP Technology for high performance On and Off-Road 4 stroke motorcycle engines. XP Technology uses an innovative highly shear stable, low volatility base oil formulation along with stable esters to achieve increased power, provide ultimate engine and transmission protection, reduce oil consumption and improve fuel economy even under race conditions. XP Technology combats engine wear and reduces friction on all critical load surfaces at both high temperature operation and on cold starts.

Application

Formulated to meet the needs of both air and water-cooled 4-Stroke engines the SILKOLENE COMP range comes in four grades and is suitable for 4-Stroke engines fitted to both On-Road and Off-Road motorcycles.

SILKOLENE COMP 4 10W-30 XP
SILKOLENE COMP 4 10W-40 XP
SILKOLENE COMP 4 15W-50 XP
SILKOLENE COMP 4 20W-50 XP

Specifications / Approvals

- JASO MA2
- API SL Performance

Advantages

- One product range suitable for all high performance 4-stroke motorcycle engines On-Road and Off-Road
- Superior shear stability produces “stay in grade” synthetic ester containing multigrade engine oils
- Provides a high degree of anti-wear performance for stressed components
- Provides enhanced high temperature deposit control resulting in a cleaner engine and thus promoting longer engine life and performance retention
- Suitable for gearboxes and transmissions where engine oil technology is specified providing good pitting protection
- Balanced frictional properties give precise clutch control / operation
- Also provides good corrosion protection, better oxidation/ nitration resistance and lower volatility than conventional products

XP
TECHNOLOGY

11% FUEL SAVINGS | **18% LOWER OIL CONSUMPTION** | **3% INCREASED POWER**

FUCHS LUBRICANTS (UK) plc
New Century Street, Hanley
Stoke-on-Trent, Staffordshire, ST1 5HU

Tel +44 (0)1782 203700
contact-uk@fuchs.com



Health, Safety and Environment - information is provided for products in the relevant Safety Data Sheet. This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products. While the information and figures given here are typical of current production and conform to specification, minor variations may occur. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the products.

Product Information



| SILKOLENE COMP 4 | Test Method | Unit | 10W-30 XP | 10W-40 XP | 15W-50 XP | 20W-50 XP |
|-----------------------------|-------------|--------------------|-----------|-----------|-----------|-----------|
| Appearance | | | Amber | Amber | Amber | Amber |
| SAE Rating | | | 10W-30 | 10W-40 | 15W-50 | 20W-50 |
| Specific Gravity at 15°C | IP160 | | 0.864 | 0.866 | 0.875 | 0.881 |
| Kinematic Viscosity@ 40°C | IP71 | mm ² /s | 73.5 | 103.6 | 134.2 | 156.9 |
| Kinematic Viscosity @ 100°C | IP71 | mm ² /s | 11.6 | 15.5 | 18.3 | 19.0 |
| Viscosity Index (VI) | IP226 | | 152 | 158 | 153 | 138 |
| Cold Crank Viscosity | ASTM D5293 | | | | | |
| 20W at -15°C | | cP | | | | 5505 |
| 15W at -20°C | | cP | | | 5406 | |
| 10W at -25°C | | cP | 4668 | 5704 | | |
| Flash point | IP 34 | °C | 215 | 212 | 212 | 220 |
| Pour point | IP15 | °C | -36 | -36 | -39 | -28 |

Updated Nov 2019 ABUK



11% FUEL SAVINGS | **18% LOWER OIL CONSUMPTION** | **3% INCREASED POWER**

FUCHS LUBRICANTS (UK) plc
New Century Street, Hanley
Stoke-on-Trent, Staffordshire, ST1 5HU

Tel +44 (0)1782 203700
contact-uk@fuchs.com



Health, Safety and Environment - information is provided for products in the relevant Safety Data Sheet. This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products. While the information and figures given here are typical of current production and conform to specification, minor variations may occur. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the products.